

PayCheck®

# Desktop 2™



The newest member of the Paycheck® series family, the Paycheck® Desktop 2™. Powered with Paycheck® NextGen™ technology, this desktop model can enhance your cage environment by providing your customers quick TITO tickets, promotional coupons and/or stream lined tax forms, to name a few, while keeping your host engaged one-on-one with your patrons.


## FEATURES

- Longest print head life
- Fastest printer in gaming
- Integrated anti-jamming paper path
- Paper low on last ticket or more (adjustable)
- PC based infrastructure
- Straight paper path
- Easy paper path access
- Multiple USB ports, MicroSD reader, HDMI, Bluetooth
- Ethernet Port
- Durable, intuitive, modular design
- Lockable Enclosure
- Standard 800 Ticket Tray
- Couponing ready
- RoHS compliant

## BENEFITS

- Better Reliability and lower overall cost
- Greater Customer Satisfaction
- Reduces paper jams no matter the bezel used
- Save on paper cost by no longer wasting tickets
- Use any fonts, images and logos for your tickets
- No jamming within a presenter
- Makes maintenance fast & easy
- Allows for easy field service and upgrades
- Network Connectivity
- Gives easy access to all major components
- Added Security
- Reduce downtime with larger ticket capacity
- Advertise your services easily
- Usable in all jurisdictions worldwide

# NANOPTIX



Side Panel for Extra Connections



Enclosure Opens Directly to the Paper Path

## DIMENSIONS (HxWxD)

- 146.3mm (5.76") x 119mm (4.69") x 335.2mm (13.20")

## WEIGHT

- 1.35 kg (3 lbs)

## PRINTING CHARACTERISTICS

- Print Speed  
250 (9.8") per second in text mode(monochrome)  
125mm (5") per second in two-color mode  
520 dots per line  
203 dots per inch  
62.5mm (2.46") print zone width (near-edge printing)  
8 dots/mm horizontal and vertical

## PAPER/MEDIA

- Type: top-coated thermal sensitive  
(Qualified for Kanzaki TO381N, Appleton Royale,  
Nashua Corporation NT 10149)
- Ticket width x length  
65mm (2.56") x 156mm (6.12") – TITO format
- Ticket thickness: 0.114-0.127mm (0.0045-0.005")
- Perf. Strength: 1.59 +/- 0.27kg (3.5 +/- 0.6 lbs)
- Monochrome or three 2-color choices: red/black, blue/black,  
green/black

## POWER REQUIREMENTS

- 24/12 VDC at 2.4A Maximum (excluding exit lamp)
- Exit lamp: 24/12 VDC
- 20mA required by lighted bezel
- Bezel port can sync up to 2A

## RELIABILITY

- Print head:  
100km or 100 million pulses for monochrome  
(approximately 640,000 TITO tickets)  
50km or 50 million pulses for 2 color

## COMMUNICATION INTERFACE OPTIONS

- Bidirectional RS-232 (up to 57.6 kbps)
- 3 Dedicated USB 2.0 Communication Ports
- 2 Slave USB 2.0 Communication Ports
- Mini-HDMI port, 1080p
- Ethernet Port
- MicroSD Card Reader
- Bluetooth
- Netplex protocol
- GDS protocol
- Windows driver

## REGULATORY INFORMATION

- CSA Ulc
- FCC Class B
- CE mark
- ICES

## ENVIRONMENTAL

- Operating temperature: 0 to 70°C (32 to 158°F)
- Storage & shipping temperature: -20 to 75°C (-4 to 167°F)
- Operating humidity: 5 to 90% RH (non-condensing)



# NANOPTIX

Toll Free: 1-888-983-3030 – Direct: 1-506-384-3388 – Email: [info@nanoptix.com](mailto:info@nanoptix.com)

[www.Nanoptix.com](http://www.Nanoptix.com)

Nanoptix and Nanoptix logo are registered trademarks of Nanoptix Inc.

All other marks are registered trademarks of their respective owners. Nanoptix reserves the right to change product specifications without notice.