

PayCheck® Puck™



With the Paycheck® Puck™, Nanoptix is proud to offer our industry leading NextGen™ technology to our existing catalog of products. The Paycheck® Puck™ brings all of the connectivity and exciting features of the Paycheck® NextGen™ TITO printer to your other Nanoptix products.

FEATURES

- Allows all Nanoptix products to take full advantage of Paycheck® Connex™
- Bring new lines of connectivity to the Paycheck® series of products as well as other printers on your floor.
- Featured Connectivity: Ethernet, HDMI, Serial, USB Host & Slave, MicroSD, etc.
- Paycheck® Puck™ has a PC Based infrastructure providing a reliable and efficient gateway for new system features and innovations.

BENEFITS

- Interconnect your whole floor and unlock your system provider's potential features and applications.
- Allows you to gradually move to new printers while still taking advantage of your existing peripherals and linking them through the Paycheck Pucks.
- Allows you to bring future proof connectivity to an existing mix of peripherals on the floor. Enhance your system capabilities without the investment of an entirely new floor of peripherals.
- The PC based infrastructure provides enhancement of system features and unlocks existing modules within your game management system.

NANOPTIX

DIMENSIONS (HxWxD)

- 35mm (1.38") x 105mm (4.13") x 105mm (4.13")

WEIGHT

- 0.195 kg (0.43 lbs)

HARDWARE SPECIFICATIONS

- 1GHz Sitara™ ARM® Cortex®-A8 32-Bit RISC Processor
- NEON™ SIMD Coprocessor
- 4GB On-Board Flash Memory
- 512MB RAM
- Linux Operating System

POWER REQUIREMENTS

- 24/12 VDC at 2.4A Maximum (excluding exit lamp)
- Exit lamp: 24/12 VDC

COMMUNICATION INTERFACE OPTIONS

- 4 Bidirectional RS-232 Ports (up to 115.2 kbps)
- 1 Dedicated USB 2.0 Communication Ports
- 1 Slave USB 2.0 Communication Ports
- HDMI port, 1080p
- MicroSD Card Reader

REGULATORY INFORMATION

- CSA Ulc
- FCC Class B
- CE mark
- ICES

ENVIRONMENTAL


- Operating temperature: 0 to 70°C (32 to 158°F)
- Storage & shipping temperature: -20 to 75°C (-4 to 167°F)
- Operating humidity: 5 to 90% RH (non-condensing)

Available with the following products:

Paycheck 4



HSV1



HSV1 Pull Tab



Paycheck HS Couponing



Spill Proof



NANOPTIX

Toll Free: 1-888-983-3030 – Direct: 1-506-384-3388 – Email: info@nanoptix.com
www.Nanoptix.com

Nanoptix and Nanoptix logo are registered trademarks of Nanoptix Inc.

All other marks are registered trademarks of their respective owners. Nanoptix reserves the right to change product specifications without notice.