

ORiZON NEXTGEN



SMARTER. FASTER. BETTER.

The ultimate kiosk printer, combining technology (PC based infrastructure), flexibility (adjustable spindle arm) and outstanding reliability (200km print head life).

FEATURES

- Prints a ticket in 0.6 seconds
- Print head life 50% more than competitors
- Available with, or without a presenter/retractor
- PC based infrastructure
- Multiple USB ports, MicroSD, HDMI, Ethernet
- Unique illuminated jamming resistant bezel
- Truly hot swappable
- Easy paper path access
- Durable, intuitive, modular design
- Diagnostic/firmware upgrade USB service port

BENEFITS

- Greater Customer Satisfaction
- Better Reliability and lower overall cost
- Automatically discards uncollected tickets
- Lower Cost of Goods, offload tasks to the printer
- Easy field service and upgrades
- Reduces paper jams for more uptime
- Easy replacement without powering down
- Able to replace paper with little or no down time
- Gives easy access to all major components
- Allows for easy field service and upgrades

NANOPTIX

DIMENSIONS (HxWxD)


- 144 x 125 x 252 mm (Printer Only)
- 144 x 125 x 310 mm (With 152mm, 6", paper roll)
- 144 x 125 x 313 mm (Printer + Presenter)
- 144 x 125 x 371 mm (With 152mm, 6", paper roll)

WEIGHT

- 1.111Kg (2.45lbs) Printer Only
- 1.452Kg (3.2lbs) Printer + Presenter

PRINTING CHARACTERISTICS

- Print Speed
250mm (9.8") per second in text mode(monochrome)
125mm (5") per second in two-color mode
640 dots per line
8 dots/mm (203 dots per inch)
80mm (3.15") print zone width (near-edge printing)
8 dots/mm horizontal and vertical



Easy paper path access to load and clear paper

PAPER/MEDIA

- Type: top-coated thermal sensitive
- Paper width options:
 - 82.5mm (3.25") wide
 - 80mm (3.15") wide
 - 60mm (2.36") wide
 - 58mm (2.28") wide
- Ticket thickness: 2.4 to 3.6 mils (54µm to 90µm)
- Maximum Paper Roll Diameter 6"
- Monochrome or three 2-color choices: red/black, blue/black, green/black
- Minimum paper core width 18mm (0.71")
- Minimum print length 65mm (2.55") w/o Presenter
- Minimum print length 85mm (3.35") w/ Presenter

POWER REQUIREMENTS

- 24 VDC at 2.4A Maximum (excluding exit lamp)
- Exit lamp: 24 VDC

RELIABILITY

- Printhead:
200km or 200 million pulses for monochrome
(approximately 1,410,000 tickets/receipts)
200km or 100 million pulses for 2 color
- Cutter:
2 million cuts

COMMUNICATION INTERFACE OPTIONS

- Bidirectional RS-232 (up to 57.6 kbps)
- 3 Dedicated USB 2.0 Communication Ports
(2 Type A and 1 Type B mini)
- HDMI port, 720p
- Ethernet Port
- MicroSD Card Reader
- Bluetooth capable
- Netplex protocol
- GDS protocol
- ESC/P
- Windows and Linux driver

REGULATORY INFORMATION

- CSA Ulc
- FCC Class B
- CE mark
- ICES

ENVIRONMENTAL

- Operating temperature: 0 to 70°C (32 to 158°F)
- Storage & shipping temperature: -30 to 70°C (22 to 158°F)
- Operating humidity: 5 to 90% RH (non-condensing)

PRESENTER / RETRACTOR

- Completes the print before feeding the ticket out of the Kiosk
- The ticket is retracted back into a discard bin within the kiosk if uncollected



NANOPTIX

Toll Free: 1-888-983-3030 – Direct: 1-506-384-3388 – Email: info@nanoptix.com

www.Nanoptix.com

Nanoptix and Nanoptix logo are registered trademarks of Nanoptix Inc.

All other marks are registered trademarks of their respective owners. Nanoptix reserves the right to change product specifications without notice.