

# PAYCHECK<sup>®</sup>

## HIGH SPEED COUPONING<sup>™</sup>



The Paycheck High Speed Couponing printer is the only voucher printer on the market which automatically prints, cuts & stacks a batch of up to 200 standard TITO tickets.

### FEATURES

- Longest print head life
- Fastest printer in gaming
- Prints, Cuts & Stacks Tickets
- Paper low on last ticket or more (adjustable)
- Approved for use in major Casino Management Systems
- Straight paper path
- Easy paper path access
- Rugged metal design
- Lockable Enclosure
- Standard 800 Ticket Tray
- Optional Ethernet Adapter
- RoHS compliant

### BENEFITS

- Better Reliability and lower overall cost
- Greater Customer Satisfaction
- Easily create a batch of voucher tickets
- Save on paper cost by no longer wasting tickets
- Quick and easy integration
- No jamming within a presenter
- Makes maintenance fast & easy
- Durable & Secure
- Added Security
- Reduce downtime with larger ticket capacity
- Network access
- Usable in all jurisdictions worldwide

# NANOPTIX

## DIMENSIONS (HxWxD)

- 192.2mm (7.5") x 178.8mm (7") x 474.9mm (18.7") with tray

## WEIGHT

- 5.5 Kg (12.1lb)

## PRINTING CHARACTERISTICS

- Print Speed  
200 (9.8") per second in text mode(monochrome)  
125mm (5") per second in two-color mode  
500 dots per line  
203 dots per inch  
62.5mm (2.46") print zone width (near-edge printing)  
8 dots/mm horizontal and vertical

## PAPER/MEDIA

- Type: top-coated thermal sensitive
- Ticket width x length  
65mm (2.56") x 156mm (6.12") – TITO format
- Ticket thickness: 0.114-0.127mm (0.0045-0.005")
- Perf. Strength: 1.59 +/- 0.27kg (3.5 +/- 0.6 lbs)
- Monochrome or three 2-color choices: red/black, blue/black, green/black

## POWER REQUIREMENTS

- 24 VDC at 2.4A Maximum (excluding exit lamp)
- Exit lamp: 24 VDC at 2A

## RELIABILITY

- Print head:  
100km or 100 million pulses for monochrome  
(approximately 640,000 TITO tickets)  
50km or 50 million pulses for 2 color
- Cutter:  
1 million Cuts

## COMMUNICATION INTERFACE OPTIONS

- Serial RS-232 Port (up to 57.6 kbps)
- USB 2.0 Communication Ports
- Ethernet Adapter (Optional)
- Netplex protocol
- Windows driver

## REGULATORY INFORMATION

- CSA Ulc
- FCC Class B
- CE mark
- ICES

## ENVIRONMENTAL

- Operating temperature: 0 to 50°C (32 to 122°F)
- Storage & shipping temperature: -20 to 60°C (-4 to 140°F)
- Operating humidity: 5 to 90% RH (non-condensing)



Lockable Cover



Automatically cuts and stacks 200 voucher tickets



USB and Serial Port

# NANOPTIX

Toll Free: +1-888-983-3030 (North America) – Direct: +1 506-384-3388 – Email: [info@nanoptix.com](mailto:info@nanoptix.com)  
[www.Nanoptix.com](http://www.Nanoptix.com)

Nanoptix and Nanoptix logo are registered trademarks of Nanoptix Inc.  
All other marks are registered trademarks of their respective owners. Nanoptix reserves the right to change product specifications without notice.