



# PAYCHECK<sup>®</sup> Slim

Designed specifically for slant and slim cabinets, the Paycheck Slim printer has 50% less depth than a regular TITO printer, making it the slimmest vertical printer on the market and the perfect choice for a space restrictive cabinet.

## FEATURES

- Slim profile
- Fastest printer in gaming
- Longest print head life
- Most standard memory in gaming printers
- Standard casing footprint
- Unique illuminated anti-jamming bezel
- RoHS compliant
- Truly hot swappable
- Easy paper path access
- Durable, intuitive, modular design
- Diagnostic/firmware upgrade USB service port

## BENEFITS

- Easy fit within small cabinets
- Greater Customer Satisfaction
- Better Reliability and lower overall cost
- Lets you personalize with fonts, images and logos
- Fast plug-and-play replacement
- Reduces paper jams for more uptime
- Usable in all jurisdictions worldwide
- Easy replacement without powering down
- Makes maintenance fast & easy
- Gives easy access to all major components
- Allows for easy field service and upgrades

# NANOPTIX

## DIMENSIONS (HxWxD)

- 248.5 x 120 x 129 mm
- 9.78 x 4.72 x 5.08 inch

## WEIGHT

- 1.215 kg (2.68 lbs)

## PRINTING CHARACTERISTICS

- Print Speed  
200mm (7.9") per second in text mode(monochrome)  
125mm (5") per second in two-color mode
- 500 dots per line
- 203 dots per inch
- 62.5mm (2.46") print zone width (near-edge printing)
- 8 dots/mm horizontal and vertical

## PAPER/MEDIA

- Type: top-coated thermal sensitive  
Ticket width x length  
65mm (2.56") x 156mm (6.12") – TITO format
- Ticket thickness: 0.114-0.127mm (0.0045-0.005")
- Perf. Strength: 1.59 +/- 0.27kg (3.5 +/- 0.6 lbs)
- Monochrome or three 2-color choices: red/black, blue/black, green/black

## POWER REQUIREMENTS

- 24 VDC at 2.4A Maximum (excluding exit lamp)
- Exit lamp: 24 VDC at 2A

## RELIABILITY

- Print head:  
100km or 100 million pulses for monochrome  
(approximately 640,000 TITO tickets)  
50km or 50 million pulses for 2 color

## COMMUNICATION INTERFACE OPTIONS

- Bidirectional RS-232 (up to 57.6 kbps)
- USB 2.0 Port
- Netplex protocol
- GDS protocol

## REGULATORY INFORMATION

- CSA Ulc
- FCC Class B
- CE mark
- ICES

## ENVIRONMENTAL

- Operating temperature: 0 to 50°C (32 to 122°F)
- Storage & shipping temperature: -20 to 60°C (-4 to 140°F)
- Operating humidity: 5 to 90% RH (non-condensing)

## CONFIGURABLE OPTIONS

- Ticket tray note sizes: 200 (Upright), 400 (Horizontal)
- Multiple bezel color options: Blue, Green, Red
- Three bezel types: Long, Short, Slanted



# NANOPTIX

Toll Free: +1-888-983-3030 (North America) – Direct: +1 506-384-3388 – Email: [info@nanoptix.com](mailto:info@nanoptix.com)  
[www.Nanoptix.com](http://www.Nanoptix.com)

Nanoptix and Nanoptix logo are registered trademarks of Nanoptix Inc.  
All other marks are registered trademarks of their respective owners. Nanoptix reserves the right to change product specifications without notice.