

ORIZON[®] NEXTGEN[™]



A COMPUTER INSIDE A PRINTER

The ultimate kiosk printer, the Orizon NextGen is a computer inside a printer. Not only is it the quickest and most durable printer of its kind, the Orizon NextGen is also an integration hub – it can integrate and power a wide range of peripherals within a kiosk solution.

FEATURES

- Includes a Linux operating system
- Prints a ticket in 0.6 seconds
- Print head life 50% more than competitors
- Diagnostic/firmware upgrade USB service port
- Multiple USB ports, MicroSD, HDMI, Ethernet
- Unique illuminated jamming resistant bezel
- Truly hot swappable
- Easy paper path access
- Durable, intuitive, modular design

BENEFITS

- Integrate and power your kiosk peripherals
- Greater Customer Satisfaction
- Better Reliability and lower overall cost
- Allows for easy field service and upgrades
- Easy field service and upgrades
- Reduces paper jams for more uptime
- Easy replacement without powering down
- Able to replace paper with little or no down time
- Gives easy access to all major components

NANOPTIX

DIMENSIONS (HxWxD)

- 89 x 118 x 95 mm (Printer Only)
- 144 x 125 x 310 mm (With 152mm, 6", paper roll)

WEIGHT

- 1.111Kg (2.45lbs) Printer Only

PRINTING CHARACTERISTICS

- Print Speed
250mm (9.8") per second in text mode(monochrome)
125mm (5") per second in two-color mode
640 dots per line
8 dots/mm (203 dots per inch)
80mm (3.15") print zone width (near-edge printing)
8 dots/mm horizontal and vertical

PAPER/MEDIA

- Type: top-coated thermal sensitive
- Paper width options:
 - 82.5mm (3.25") wide
 - 80mm (3.15") wide
 - 60mm (2.36") wide
 - 58mm (2.28") wide
- Ticket thickness: 2.4 to 3.6 mils (61µm to 91µm)
- Maximum Paper Roll Diameter 6"
- Monochrome or three 2-color choices: red/black, blue/black, green/black
- Minimum paper core width 18mm (0.71")
- Minimum print length 65mm (2.55")

POWER REQUIREMENTS

- 24 VDC at 2.4A Maximum (excluding exit lamp)
- Exit lamp: 24 VDC

RELIABILITY

- Printhead:
200km or 200 million pulses for monochrome (approximately 1,410,000 tickets/receipts)
200km or 100 million pulses for 2 color
- Cutter: 2 million cuts

HARDWARE SPECIFICATIONS

- 1 GHz Sitara ARM cortex-A8 RISC Processor
- NEON SIMD Coprocessor
- 4 GB on-board Flash
- 512 MB RAM
- Running Linux TI Distro

COMMUNICATION INTERFACE OPTIONS

- Bidirectional RS-232 (up to 57.6 kbps)
- 3 Dedicated USB 2.0 Communication Ports (2 Type A and 1 Type B mini)
- HDMI port, 720p
- Ethernet Port
- MicroSD Card Reader
- Bluetooth capable
- Netplex, GDS, & ESC/P protocol support available
- Windows and Linux driver

REGULATORY INFORMATION

- CSA Ulc
- FCC Class B
- CE mark
- ICES

ENVIRONMENTAL

- Operating temperature: 0 to 70°C (32 to 158°F)
- Storage & shipping temperature: -30 to 70°C (22 to 158°F)
- Operating humidity: 5 to 90% RH (non-condensing)

NANOPTIX

Toll Free: +1-888-983-3030 (North America) – Direct: +1 506-384-3388 – Email: info@nanoptix.com

www.Nanoptix.com

Nanoptix and Nanoptix logo are registered trademarks of Nanoptix Inc.

All other marks are registered trademarks of their respective owners. Nanoptix reserves the right to change product specifications without notice.