



PAYCHECK[®] TERMINAL XL[™]

PayCheck[®] Terminal[™] XL is the world's first Kiosk terminal powered by a TITO printer. Taking advantage of the power and uniqueness of the Paycheck[®] NextGen[™] printer, we created a Linux based terminal for your gaming, lottery and retail applications.

FEATURES

- Linux based Software Development Kit (SDK) to implement your applications
- Built around the Paycheck[®] NextGen[™] Printer
- Lockable standard 800 Ticket Tray TITO paper
- 10 inch full-color LCD screen
- Capacitive multi-touchscreen
- High performance 1-D and 2-D bar code scanner
- Smart card reader with RFID
- USB on-the-go, MicroSD reader, Ethernet, Bluetooth
- Fastest printer in gaming
- Integrated anti-jamming paper path
- Paper low: "last ticket out" or adjustable
- Small footprint (335mmx150mm)

BENEFITS

- Variety of applications:
 - Sports Betting Kiosk
 - Players Loyalty Kiosk
 - Pull Tab Kiosk
 - Self-Serve Terminal for Lottery
 - Promotional Kiosk
- SDK compatible with your GMS provider and/or marketing promotional provider
- Ideal for desktop or self-serve application
- Maximizing space with its small footprint
- Networkable
- Advertise your services easily
- Reduce downtime with large ticket capacity

NANOPTIX

HARDWARE CHARACTERISTICS

- 1 GHz Sitara™ ARM® Cortex®-A8 32-bit RISC Processor
- NEON™ SIMD Coprocessor
- 4 GB on-board flash
- 512MB on-board RAM

POWER REQUIREMENTS

- 24 VDC at 2.4A Maximum

DISPLAY CHARACTERISTICS

- 10.1 inches full-color a-Si TFT with IPS technology
- Display colors: 262K (6-bits per color)
- Native resolution: 1280x800 pixels, Aspect ratio: 16:10
- Viewing angle: 89 deg all directions
- Brightness: 400 cd/m2 (nits), Contrast ratio: 800:1
- Ambient light sensor for automatic brightness control
- Capacitive touch screen (multi-touch optional)
- Display tilt angle: 20 deg to 70 deg from vertical

SCANNER CHARACTERISTICS

- ZEBRA SE4710 Intelligent imaging technology
- Capture virtually any 1-D or 2-D bar code in milliseconds
- Capture from near contact to farther than 24 in. (60cm)
- Photo capture capability with resolution of 1280 x 800 pixels

SMART CARD READER CHARACTERISTICS

- Support contactless and contact smart cards
- 13.56 MHz RFID technology
- Smart Card Interfaces: PICC (Contactless), ICC (Contact), SAM
- Supported Card Types: ISO 14443 Type A and B Mifare Classic, Mifare Plus, Mifare DESFire EV1, ISO 7816 Class A, B, C Memory Cards
- Certifications/Compliance: ISO 14443, ISO 7816, FIPS 201, CE, FCC, RoHS, PCSC, CCID, Microsoft WHQL

PAPER/MEDIA

- Ticket: 65mm (2.56") x 156mm (6.12") – TITO format
- Type: top-coated thermal sensitive

PRINTING CHARACTERISTICS

- Print Speed: 250 (9.8") per second in text mode
- 62.5mm (2.46") print zone width (near-edge printing)
- 8 dots/mm horizontal and vertical

PRINTER RELIABILITY

- Printhead:
100km or 100 million pulses for monochrome
(Approximately 640,000 TITO tickets)
50km or 50 million pulses for 2 color

COMMUNICATION INTERFACE OPTIONS

- 2 Slave USB 2.0 Communication Ports
- Ethernet Port
- MicroSD Card Reader
- Bluetooth

REGULATORY INFORMATION

- CSA/UL
- FCC Class B
- CE mark
- ICES

ENVIRONMENTAL

- Operating temperature: 0 to 70°C (32 to 158°F)
- Storage & shipping temperature: -20 to 75°C (-4 to 167°F)
- Operating humidity: 5 to 90% RH (non-condensing)

DIMENSIONS (HxWxD)

- Paycheck® Terminal XL™
 - 282mmx282mmx335mm
(11.1in x 11.1in x 13in)

WEIGHT

- Paycheck® Terminal™ - 2.64 Kg (5.81 lbs)



NANOPTIX

Toll Free: +1-888-983-3030 (North America) – Direct: +1 506-384-3388 – Email: info@nanoptix.com

www.Nanoptix.com

Nanoptix, Paycheck NextGen and NextGen Terminal are trademarks and registered trademarks of Nanoptix Inc. All other marks are registered trademarks of their respective owners. Nanoptix reserves the right to change product specifications without notice. NextGen Terminal patent pending. ©2019 Nanoptix. All rights reserved.